



Product Overview

GTD-150S is a product that meets the highest standards in street lighting. It provides safe and effective lighting with its powerful light emitting capacity and long-lasting LED technology.

Opsiyonlar

- Emergency Kit: Yes (1-3 hours)
- Dimming Protocol: Available

STREET LIGHTING GTD 150S

GTD-150S100

GTD-150S125

GTD-150S150

GTD-150S170



Technical Specifications

- Product body; aluminum injection
- Tempered Glass
- Lighting Surge Protector: 5kV - 20kV
- Excellent thermal performance
- Lifetime: >75,000 hours, PF: >95%
- 90° adjustable mounting angle
- Input Voltage : 180-240V Frequency: 50-60 Hz
- Color rendering ind. (CRI): >70
- Power factor: >0.95
- 3 year warranty.

Areas of Use

Urban Roadways

Building Environments

Parks

Squares

Public Parking Lots

PRODUCT CODE	Power (W)	LUMINOUS FLUX (lm)	COLOR TEMPERATURE (K)	PRODUCT WEIGHT (kg)	PRODUCT DIMENSIONS (mm)	GROSS WEIGHT (kg)	BOX DIMENSIONS (mm)
GTD-S-150S100	100	11700	3000-6500	6,7	295*620*152	7,3	670*335*190
GTD-S-150S125	125	14625	3000-6500	6,7	295*620*152	7,3	670*335*190
GTD-S-150S150	150	17550	3000-6500	6,7	295*620*152	7,3	670*335*190
GTD-S-150S170	170	19890	3000-6500	6,7	295*620*152	7,3	670*335*190